

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
13 October 2005 (13.10.2005)

PCT

(10) International Publication Number
WO 2005/094248 A3

(51) International Patent Classification:

B66B 1/34 (2006.01) B66B 3/00 (2006.01)

(21) International Application Number:

PCT/US2004/007900

(22) International Filing Date: 16 March 2004 (16.03.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(71) Applicant (for all designated States except US): **OTIS ELEVATOR COMPANY** [US/US]; Ten Farm Springs Road, Farmington, CT 06032 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **STUCKY, Paul, A.** [US/US]; 1038 Melbourne Avenue, Stockton, CA 95203 (US). **KRYZMAN, Michael, A.** [US/US]; 34 Hammick Road, West Hartford, CT 06107 (US). **VERONESI, William, A.** [US/US]; 342 Fairfield Ave., Hartford, CT 06114 (US).

(74) Agent: **GASKEY, David, J.**; Carlson, Gaskey & Olds, 400 W. Maple Rd., Suite 350, Birmingham, MI 48009 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM,

AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:

— of inventorship (Rule 4.17(iv))

Published:


— with international search report

(88) Date of publication of the international search report:

3 August 2006

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: ELEVATOR LOAD BEARING MEMBER MONITORING DEVICE



(57) Abstract: An elevator load bearing member (30) monitoring device includes a controller (42) that applies a selected electrical signal to tension members (32) of the load bearing member (30). In one example, connectors (40) are associated with ends of the load bearing member (30) to establish an electrical interface between the controller (42) and the tension members (32). The connectors (40) facilitate establishing electrical circuit loops along the tension members (32) such that only non-adjacent tension members are energized at a selected time. A variety of circuit configurations are disclosed. The applied electrical signal in one example has a potential that is negative compared to a ground potential of a hoistway in which the elevator belt is used. In another example, the electrical signal comprises a plurality of pulses and has a duty cycle that is on the order of about one percent.

WO 2005/094248 A3